



# 1950 siaspeed

for a perfect finish at full speed



### for a perfect finish at full speed

The versatile all-round product 1950 siaspeed is specially designed for high stock removal rates, perfect surface quality and long life in applications such as the surface treatment of body filler, primer filler, lacquers and paints.

- ▶ Very high stock removal rates and excellent finish
- ▶ Performance-enhancing grit mix with ceramic corundum in 40 - 80 grit range
- ▶ Minimal clogging thanks to open coating in 220 - 600 grit range
- ▶ Extremely long lifetime
- ▶ Lower abrasive consumption
- ▶ Versatile all-round product with an attractive range of options

#### Product profile

|                  |   |             |
|------------------|---|-------------|
| Grit type:       | Mixed grit with ceramic content           | 40 – 80     |
|                  | Semi-friable aluminium oxide / blue-fired | P100 – P600 |
| Grit range:      | 40; 60-600                                |             |
| Backing:         | Paper                                     |             |
| Coating:         | Electrostatic                             | 40 – P180   |
|                  | Electrostatic open                        | P220 – P600 |
| bonding:         | Resin over resin                          |             |
| Special coating: | Stearate                                  | from 80     |

#### Use



#### Applications

- Sanding off coatings and impurities
- Sanding out unevenness at the edges of repaired surfaces
- Flattening bodyfiller and composite materials
- Fine sanding primer filler
- Keying old and new lacquers

#### Materials

Colour; Primer filler; Bodyfiller; Lacquer; Old lacquer; Primer coat; Epoxy primer coat; Cathodic dip primer coat; Plastics; Acrylic glass (Plexiglass); Gelcoat polyester; Glass-fibre reinforced plastic (GRP)

#### Technology

Open coating; siafast; siasoft; S Performance



# 1950 siaspeed

for a perfect finish at full speed



## for a perfect finish at full speed

The versatile all-round product 1950 siaspeed is specially designed for high stock removal rates, perfect surface quality and long life in applications such as the surface treatment of body filler, primer filler, lacquers and paints.

- ▶ High-performance abrasives
- ▶ High removal rate
- ▶ Longest lifetime
- ▶ A versatile all-round product
- ▶ Lower abrasive consumption
- ▶ Homogeneous sanding finish

### Product profile

|                  |  |                          |
|------------------|--|--------------------------|
| Grit type:       | Mixed grit with ceramic content<br>Semi-friable aluminium oxide / blue-fired | 40 – 80<br>P100 – P600   |
| Grit range:      | 40; 60-600   |                          |
| Backing:         | Paper  |                          |
| Coating:         | Electrostatic<br>Electrostatic open  | 40 – P180<br>P220 – P600 |
| bonding:         | Resin over resin   |                          |
| Special coating: | Stearate   | from 80                  |

### Use



### Applications

- Keying polyesters and composites
- Sanding out feather edges, flash rust and stone chips
- Shaping of bodyfillers and primer fillers
- Keying new components and factory primers
- Sanding of old lacquer
- Scuffing of old and new lacquers for blending
- Flattening bodyfiller and primer filler

### Materials

Colour; Primer filler; Bodyfiller; Lacquer; Old lacquer; Primer coat; Epoxy primer coat; Cathodic dip primer coat; Plastics; Acrylic glass (Plexiglass); Gelcoat polyester; Glass-fibre reinforced plastic (GRP)

### Technology

Open coating; siafast; siasoft; S Performance



# 1950 siaspeed

for a perfect finish at full speed



### for a perfect finish at full speed

The versatile all-round product 1950 siaspeed is specially designed for high stock removal rates, perfect surface quality and long life in applications such as the surface treatment of body filler, primer filler, lacquers and paints.

- ▶ A versatile all-round product
- ▶ High removal rate
- ▶ Longest lifetime
- ▶ Minimal clogging thanks to open coating in 220 - 600 grit range

#### Product profile

|                  |   |             |
|------------------|---|-------------|
| Grit type:       | Mixed grit with ceramic content           | 40 – 80     |
|                  | Semi-friable aluminium oxide / blue-fired | P100 – P600 |
| Grit range:      | 40; 60-600                                |             |
| Backing:         | Paper                                     |             |
| Coating:         | Electrostatic                             | 40 – P180   |
|                  | Electrostatic open                        | P220 – P600 |
| bonding:         | Resin over resin                          |             |
| Special coating: | Stearate                                  | from 80     |

#### Applications

- Sanding out uneven areas such as scratches or marks

#### Materials

Lacquer; Hardwood; Softwood; Solid surface material; Primer filler; Bodyfiller; Resinous wood; Plaster; Plasterboard; Plastics

#### Technology

Open coating; siafast; siasoft; S Performance

#### Use

